



US009638493B2

(12) **United States Patent**
Bowman

(10) **Patent No.:** **US 9,638,493 B2**
(45) **Date of Patent:** ***May 2, 2017**

(54) **POINTING DEVICES, APPARATUS,
SYSTEMS AND METHODS FOR HIGH
SHOCK ENVIRONMENTS**

(71) Applicant: **Orval E. Bowman**, Chuluota, FL (US)

(72) Inventor: **Orval E. Bowman**, Chuluota, FL (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **14/577,179**

(22) Filed: **Dec. 19, 2014**

(65) **Prior Publication Data**

US 2015/0096217 A1 Apr. 9, 2015

Related U.S. Application Data

(60) Continuation-in-part of application No. 14/513,809,
filed on Oct. 14, 2014, now Pat. No. 9,270,082, which
is a division of application No. 14/089,041, filed on
Nov. 25, 2013, now Pat. No. 9,077,139, which is a
division of application No. 13/442,425, filed on Apr.
9, 2012, now Pat. No. 8,826,582.

(60) Provisional application No. 61/629,737, filed on Nov.
26, 2011.

(51) **Int. Cl.**

F41G 1/35 (2006.01)

F41G 11/00 (2006.01)

F41G 1/36 (2006.01)

(52) **U.S. Cl.**

CPC **F41G 1/35** (2013.01); **F41G 11/005**
(2013.01); **F41G 1/36** (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,189,766 A	2/1940	Unertl	
2,440,260 A	4/1948	Gall	
2,817,968 A	12/1957	Schmitz	
3,096,655 A	7/1963	Peterson	
3,189,775 A *	6/1965	Fyler	H01J 29/823 335/212

(Continued)

FOREIGN PATENT DOCUMENTS

WO 9942783 8/1999

OTHER PUBLICATIONS

Bowman, Pointing Devices, Apparatus, Systems and Methods for
High Shock Environments, U.S. Appl. No. 14/577,179, filed Dec.
19, 2014, Office Action Summary mailed Sep. 3, 2015, 8 pages.

(Continued)

Primary Examiner — Stephen M Johnson

(74) *Attorney, Agent, or Firm* — Brian S. Steinberger;
Law Offices of Brian S. Steinberger, P.A.

(57)

ABSTRACT

Devices, apparatus, systems and methods for providing
accurate linear and angular positioning with a payload
mounted to a beam having freely moveable ends. The
payload can be a laser pointer mounted on a firearm, which
maintains the initial precise pointing during and after expo-
sure in high G shock and vibration environments. Vertical
and lateral adjustment controls can adjust minute changes in
beam orientation. Precision adjustments can be performed in
a zero G, one G, or high G environment and maintains the
adjustment during and after being exposed to a high G shock
or vibration environment.

14 Claims, 29 Drawing Sheets

